

JC07 Rec'd PCT/PTO 15 DEC 2001

FORM PTO-1390 (REV. 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER PLI-1052	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (If known, see 37 CFR 1.5) 10/018877	
INTERNATIONAL APPLICATION NO. PCT/US00/40244		INTERNATIONAL FILING DATE 19 June 2000 (19.06.00)		PRIORITY DATE CLAIMED 18 June 1999 (18.06.99)	
TITLE OF INVENTION SHOE WEAR INDICATOR					
APPLICANT(S) FOR DO/EO/US MYERS, Steven and STRASSER, Michael					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. 4. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> has been communicated by the International Bureau. c. <input checked="" type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> a. <input type="checkbox"/> is attached hereto. b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). 					
Items 11 to 20 below concern document(s) or information included:					
<ol style="list-style-type: none"> 11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input type="checkbox"/> A FIRST preliminary amendment. 14. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 15. <input type="checkbox"/> A substitute specification. 16. <input checked="" type="checkbox"/> A change of power of attorney and/or address letter. 17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 20. <input checked="" type="checkbox"/> Other items or information: a set of FORMAL drawings 					

U.S. APPLICATION NO. (If known) 10/018074		INTERNATIONAL APPLICATION NO. PCT/US00/40244		ATTORNEY'S DOCKET NUMBER PLI-1052	
--	--	---	--	---	--

21. The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO. **\$1000.00**

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO **\$860.00**

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO **\$710.00**

International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) **\$690.00**

International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) **\$100.00**

ENTER APPROPRIATE BASIC FEE AMOUNT =

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$
Total claims	24 - 20 =	4	x \$18.00	\$ 72.00
Independent claims	3 - 3 =	0	x \$80.00	\$ -0-
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$270.00
TOTAL OF ABOVE CALCULATIONS =				\$ 812.00
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				+ \$ 406.00
SUBTOTAL =				\$ 406.00
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$ -0-
TOTAL NATIONAL FEE =				\$ 406.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$ -0-
TOTAL FEES ENCLOSED =				\$ 406.00
				Amount to be refunded: \$
				charged: \$

CALCULATIONS PTO USE ONLY

a. ☒ A check in the amount of \$ 406.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☐ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. _____. A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Albert O. Cota
5460 White Oak Avenue
Suite A-331
Encino, California 91316

SIGNATURE

Albert O. Cota

NAME

29,291

REGISTRATION NUMBER

Shoe Wear Indicator

5 TECHNICAL FIELD

The present invention relates to shoes capable of indicating the approximate remaining useful life of the shoes, and more specifically, to shoes capable of recording data relating to impacts experienced by the shoe, using the collected data to estimate
10 the remaining useful life of the shoe, and displaying the results in a manner visible or audible to the user.

BACKGROUND ART

15 Shoes are generally considered to be an essential item of apparel by most people for reducing the likelihood of injury, particularly when engaging in activities such as sports and running.

A typical generic athletic or active wear shoe includes a relatively soft and
20 flexible upper portion for surrounding at least part of the wearers foot, including a pair of side flaps which define a foot recess, a shoe tongue extending between the side flaps, and a means for securing the shoe side flaps to each other. Such shoes typically further include a sole to provide protection from and cushion against uncomfortable contact with a supporting surface such as the ground. The sole will typically further
25 comprise a series of layers of differing materials with differing characteristics, such as

a tough outsole component, a cushioned midsole component, and a soft insole component. The sole is typically affixed on its upper surface to the lower margin of the upper portion of the shoe by the use of an adhesive.

5 The midsole of conventional shoe construction functions as a shock absorber to cushion impacts experienced by the user's foot, and will deform in response to force exerted against it. The compression and decompression characteristics of the midsole layer are important both for protecting the user, and for the longevity of the shoe. The shock absorbing capability of the midsole of conventional shoes tends to
10 progressively deteriorate with use. Consumers of shoes, particularly athletic shoes and running shoes, are concerned with knowing when a shoe needs to be replaced. Wear on the outsole can be easily checked with an occasional visual inspection of the sole of the shoe. However, it is often difficult to tell when a shoe has lost its ability to provide sufficient cushioning or shock-absorbing effects.

15

Failure to replace shoes when the shock-absorbing abilities of the shoe have deteriorated may result in severe or disabling injuries. On the other hand, athletic shoes are generally perceived to be very expensive and premature retirement of shoes by as little as 5% to 10% of the anticipated life of the shoes may result in the
20 perception of a significant unwarranted expense or cost to the consumer.

Prior efforts have been made to develop a shoe that would indicate when the shock-absorbing ability of the shoe has deteriorated, and that the shoe must be

experienced by the sensor. In other embodiments the shoe comprises at least two sensors. In such embodiments, it is preferable that at least one sensor be positioned in the sole of the shoe proximate the heel, and another in the sole of the shoe proximate the ball of the foot.

5

In some preferred embodiments the shoe further comprises a button or switch to activate the display. In a further preferred embodiment, the shoe further includes a resistor network between the sensor and the operational circuitry. In some embodiments, the operational circuitry may comprise a microprocessor. The resistor
10 network preferably converts the signal to a useable voltage and converts the signal to a form able to be used by digital electronics, and the resistor network preferably sends signals to the operational circuitry which allow the detection and differentiation of signals of varying signal strength received from the sensors.

15 The sensors may comprise a piezoelectric element, and may further comprise a rigid element positioned in contact with, or near the piezoelectric element to enhance the deformation of the piezoelectric element. The rigid element preferably extends transversely across the upper surface of the piezoelectric element, although in alternate embodiments the rigid element may be positioned effectively in other
20 locations.

The display may be visual or audible or both, and in alphanumeric or graphical format. The display used may include light emitting diodes, electroluminescent

panels, liquid crystal displays, flexible liquid crystal displays, or any other kinds of displays adaptable for use in the invention.

The invention further comprises a method for estimating the approximate
5 useful remaining life of the shock absorbing capability of the shoe, wherein the shoe
comprises at least one sensor, operational circuitry in communication with the sensor,
wherein the operational circuitry is capable of manipulating data received from the
sensor to estimate a remaining life of the shock absorbing capabilities of the shoe, a
power source electrically coupled to the operational circuitry, and a display in
10 communication with the operational circuitry capable of displaying information
related to the remaining useful life of the shock absorbing capabilities of the shoe; the
method comprising the following steps: (a) providing a pre-determined numerical
value; (b) receiving a signal; (c) applying an algorithm to derive a value; (d) adding
the numerical value of step (c) to a sum of such values to create a new value; (e)
15 comparing the new value of step (d) to the pre-determined value of step (a); (f)
estimating the remaining life of the shock absorbing ability of the shoe based on the
results of the comparison in step (e).

The method of the invention may also comprise the step of (g) displaying the
20 remaining life of the shock absorbing capability of the shoe based on the results of the
comparison in step (e). In another embodiment, the signal from the sensor may be
conditioned before step (b). Also, the method of the invention may be performed
separately for separate sensors.

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 shows a cutaway side view of an athletic shoe according to the invention.

FIG. 2 shows a block diagram of an embodiment of circuitry of the invention.

10

FIG. 3a shows a cutaway side view of the sole of a typical athletic shoe with an embodiment of the impact sensor in a neutral position.

FIG. 3b shows a cutaway side view of the sole of a typical athletic shoe with an embodiment of the impact sensor while being deflected.

15

FIG. 4 shows a schematic of an embodiment of the impact detection circuitry of the invention.

20 FIG. 5 shows a perspective view of the upper of the heel of an embodiment of the invention.

FIG. 6 shows a perspective view of an alternate embodiment of the upper of the heel of an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

5 The present invention is a shoe including one or more impact sensors to provide data relating to impacts experienced by the shoe. The shoe further includes apparatus for collecting, storing, and analyzing the data in order to estimate the remaining useful life of the shoe, and that displays or conveys the results in a form comprehensible by the user of the shoe.

10

 The invention will be described by reference to the Figures 1 through 7, wherein like numbers refer to similar features. Although the Figures and the following detailed description show and discuss the invention in use on a typical athletic shoe, it is understood that the invention could be incorporated into any kind of footwear, including but not limited to dress shoes, boots, sandals, slippers, overshoes, and the like. Furthermore, the particular configuration of the shoe, and the method of making the shoe, are not critical to the invention, and any known and acceptable methods or means for manufacturing the shoe may be used.

20

 FIG. 1 shows a cutaway side view of a conventional generic athletic shoe 100 constructed in accordance with a preferred embodiment of the invention. The conventional athletic shoe 100 includes a relatively soft and flexible upper portion 102 for surrounding at least part of the wearers foot, including a pair of side flaps which define a foot recess, a tongue 106 extending between the side flaps, and a means for

securing the shoe side flaps to each other. Typically, laces are threaded through a plurality of lace eyelets disposed along parallel opposing sides of the flaps to secure the shoe 100, however, other fastening means such as known hook and loop fastener straps or elastic materials may be used. The shoe 100 further includes a sole 110 to
5 provide protection from and cushion against uncomfortable contact with a supporting surface such as the ground. Typical materials used in the upper portion 102 of the shoe 100 include leather and man made sheet materials such as polyvinyl or polyurethane sheets, or a combination thereof. The particular materials used in the upper portion 102 of the shoe 100 are not critical to the invention. These materials
10 may be die-cut or laser-cut and stitched over a foot shaped last to form the finished upper portion 102. The sole 110 is typically molded or formed from one or more elastomeric materials such as foamed or solid polyurethane or ethylene vinyl acetate, and are configured to include common structural features such as a top or footbed surface, a peripheral outer or side wall surface, and a bottom or ground contacting
15 surface. The particular configuration of the sole 110 of the shoe 100 is not critical to the invention. The sole of a typical simple athletic shoe will typically comprise a series of layers of differing materials with differing characteristics. The shoe 100 of FIG. 1 includes a tough outsole 112, a cushioned midsole 114, and an insole 116. The sole 110 is typically affixed on its top surface to the lower margin of the upper portion
20 102 of the shoe 100 by the use of an adhesive.

A key element of the invention is the ability of the shoe 100 to monitor impacts experienced by the shoe 100, which allows an estimation of the remaining life of the shock absorbing capability of the shoe 100 based on analysis of the collected

impact data. Thus, the invention deviates from a conventional shoe design in having certain apparatus associated with the shoe 100 for performing the desired function. Referring to FIG. 1, the major components include at least one force or impact sensor 120, operational circuitry 122 to manipulate the data received from the impact sensors 120, display apparatus 124 for displaying a signal from the operational circuitry 122 either in audible or visual form, and a power source 126 to provide the necessary electric power. The invention also preferably includes a switch or button 128 for activating the display 124. FIG. 2 shows a block diagram of an embodiment of circuitry of the invention of FIG. 1.

10

Referring to FIG. 1, at least one impact sensor 120 is preferably located under either the ball of the foot or the heel, however, it is preferred that two or more impact sensors 120 be used, so that at least one impact sensor 120 is located under both the heel and the ball of the foot. The impact sensor 120 is preferably molded into the midsole 114 of the shoe 100, although in alternate embodiments the impact sensor 120 could be located elsewhere. For example, the impact sensors 120 may be located in the insole 116, or under the insole 116 but above the midsole 114, or adjacent to the outsole 112, or in any other desired location. In some alternate embodiments, it may be desirable to use an accelerometer as the impact sensor 120 located in the upper portion 102 of the shoe.

20

Impact sensors, pressure sensors, accelerometers and the like are generally well known, and many kinds of such devices may be useable in the present invention. It is preferable that the sensor 120 be inexpensive, easily customizable for different

shoe designs and configurations, and compact in size for easy incorporation into various shoe designs. Because the impact sensors 120 are preferably embedded in the sole 110 of the shoe 100 and may not be easily replaceable, it is preferable that the impact sensors 120 be rugged and resistant to mechanical fatigue. In preferred
5 embodiments of the invention the impact sensors 120 can also sense the magnitude of the force of the impact experienced by the shoe 100, and provide a signal that conveys data regarding the force of the impact.

Piezoelectric force sensors have been found to typically include the desired
10 characteristics discussed above, and LDT-0 piezo ceramic material made by Measurements Specialties Incorporated has been used successfully in prototypes. If a single sensor 120 is inadequate to provide the desired signal strength, additional sensors 120 may be used to increase the signal strength. Additional sensors 120 may also be used to improve the monitoring of the shoe wear. FIGS. 3a and 3b, show one
15 preferred embodiment of an impact sensor 120 wherein the sensor 120 comprises a laminate piezoelectric sheet element 132 with a rigid element 134 positioned above the piezoelectric sheet element 132. Referring to FIG. 3a an impact sensor 120 is shown in a neutral position with the rigid element 134 laminated onto the piezoelectric sheet element 132. In alternate embodiments, other configurations may
20 be used, or the rigid element 134 may simply comprise a local higher density foam. In the embodiment shown, the sensor 120 is positioned between the midsole 114 and the insole 116 of the sole 110 of the shoe 100. When a wearer takes a step, for example, the impact of the step will cause the foot to compress the compressible midsole 114 of the sole 110 of the shoe 100 as seen in FIG. 3b. This compression will cause a

deflection of the piezoelectric sheet element 132 of the impact sensor 120. The rigid element 134 increases the localized deflection of the piezoelectric sheet element 132. The deflection of the piezoelectric sheet element 132 generates a current proportional to the degree of deflection, and thus proportional to the force of the impact experienced by the sensor 120.

Referring to FIG. 2, The impact sensors 120 are electrically coupled to the operational circuitry 122, which preferably includes some kind of microprocessor 140. The current output from an impact sensor 120 configured as set forth above is quite low, possibly as low as one micro amp. The small varying levels of current output from the sensor 120 must be detected by the microprocessor 140. Conventional design techniques suggest the use of an amplifier to convert the low current to useable voltage. However, a suitable amplifier would be prohibitively expensive. The preferred solution is to use a resistor divider network 142 in conjunction with the inherent characteristics of the microprocessor input pins 144 to detect varying levels of sensor 120 current output. The voltage of the system is equal to the current from the sensors 120 multiplied by the resistance of the resistor network 142, and the use of high impedance resistors in the resistor network 142 allows the generation of a useable voltage level from the low current provided by sensors 120, which also has the simultaneous effect of performing an analog to digital signal conversion.

FIG. 4 shows a schematic of a preferred embodiment of the circuitry of the resistor network 142 including a series of high impedance resistors 146 configured such that a number of microprocessor input pins 144 are connected between the

resistors 146. Only a single impact sensor 120 with a three threshold level resistor network 142 is shown in FIG. 4. However, in alternate embodiments, the as little as one threshold level could be used, and any number of sensors 120 may be used, and the sensors 120 may aggregate the signals to a single resistor network 142, or the
5 sensors 120 may have separate resistor networks 142, or a combination thereof, depending on what is being accomplished with a given sensor 120. Furthermore, the threshold levels may be the same or different for different sensors 120, and the number of thresholds may be varied between sensors 120 as desired. For example, in some embodiments, it may be desirable to use only two threshold levels for the sensor
10 120 under the ball of the foot in the shoe 100, but to use three threshold levels for the sensor under the heel of the foot in the shoe 100.

The individual resistor 146 impedance values are chosen such that the logical high input condition of selected input pins 144 are met when a certain selected impact
15 threshold is reached. Thus, the impedance values of the resistors 146 are preferably not identical. The threshold values selected are preferably determined by reference to test data obtained from actual tests performed on actual shoes 100, or on the materials used in the shoes 100.

20 In the case of a three threshold system as shown in FIG. 5, a low threshold signal, for example a signal generated by a walking impact, would be sensed when the sensor 120 output current is sufficiently high to generate a voltage that meets or exceeds the logic high voltage of only one input pin 144.

A medium threshold signal, such as a signal generated by a running impact for example, would be sensed when the sensor 120 output current is sufficiently high to generate a voltage that meets or exceeds the logic high voltage of only two input pins 144.

5

A high threshold signal, for example a signal generated by a jumping or sprinting impact, would be sensed when the sensor 120 output current resulted in a voltage that is sufficiently high to generate a voltage that meets or exceeds the logic high voltage for all three input pins 144.

10

As previously stated, the operational circuitry 122 preferably comprises an integrated circuit device such as a microprocessor 140 formed using conventional or known integrated circuit manufacturing techniques. The operational circuitry 122 is preferably positioned at a location in the sole 110 of the shoe 100 that experiences as little flexure or stress as possible. However, in alternate embodiments the operational circuitry 122 could be positioned virtually anywhere on the shoe 100. As has been explained, it is the primary object of the invention to calculate and display an estimated remaining useful life of the shock absorbing capabilities of the shoe 100. However, in alternate embodiments, the sensors 120 and the operational circuitry 122 may also be used to sense, analyze, and display other kinds of data of interest to the user, and to perform other data analysis functions relating to the use the shoe 100.

20

Based on the environment in which the operational circuitry 122 must function, it is preferable that the operational circuitry 122 has low power requirements

to reduce the demand on the power source 126. It is currently preferred that the operational circuitry 122 operate on a voltage range between 1 and 9 volts, and more preferably approximately 3 volts. It is also preferable that the operational circuitry 122 be inexpensive, compact in size, and easily customizable for integration into various shoe 100 designs. Finally, it is also preferable that the operational circuitry 122 be rugged and resistant to mechanical fatigue. The operational circuitry 122 can be assembled from off the shelf or customized components. In alternate embodiments, it may be necessary or desirable to include a voltage limiting device to protect the operational circuitry from high sensor output levels.

10

In prototypes, a Microchip PIC 16C505 microprocessor, mounted on a small board including the resistor network 142, has been used successfully as the microprocessor 140 in the operational Circuitry. In alternate embodiments, much of the operational circuitry 122 may be placed in a single ASIC (Application Specific Integrated Circuit) or other custom circuitry with ease. In this embodiment, it is preferred that the ASIC or other custom circuitry have a low cost surface mount package to reduce manufacturing costs, and the resistor network 142 is preferably formed in the ASIC or other custom circuitry. The circuit board may also include a fixture to hold the power source 126. However, in alternate embodiments the power source 126 may be a separate component. The LEDs are wired to the circuit board and are in electrical communication with the power source 126 and the operational circuitry 122 which controls the lighting of the LEDs 152 in response to a wear status request, i.e. activation of the display by depressing button 128. Many modifications to the circuit may be easily made by those skilled in the art.

The power source 126 is preferably mounted on the board of the operational circuitry 122, and is in electrical communication with the operational circuitry 122. A three volt lithium coin cell was used successfully in prototypes. However, many
5 known battery types may be useable or preferred. The preferred battery will be small, inexpensive, and will last for the life of the shoe 100. In alternate embodiments other power sources 126 may be used, including solar panels or fuel cells. In still other embodiments, the power source 126 may be replaceable or rechargeable. In further
10 embodiments, the invention may be powered by the current generated by the sensors, or by other piezoelectric elements. In embodiments using a rechargeable battery, the battery may be charged by the sensors or other piezoelectric elements associated with the shoe, or the battery may be recharged inductively or by a solar panel or other recharge source.

15 The invention also comprises a display apparatus 124 for displaying a signal from the operational circuitry 122 either in a form that may be perceived by the user, including audible, visual, or tactile form. The wires to the display 124 may be molded into the shoe 100 and may be routed by any acceptable path through the sole 110 of the shoe 100. The display 124 may be located at any convenient location on the shoe
20 100 or on the upper 102 of the shoe 100, but is preferably located at the heel 108 of the upper 102 of the shoe 100 as seen in FIGS 6 and 7. The location of display 124 selected will depend both on functional and ornamental factors in the design of the shoe 100.

The preferred display 124 is inexpensive, rugged, waterproof, dust proof, impact resistant, compact in size, easily customizable for different shoe designs, and uses little power. Although it is possible to design the shoe 100 such that the display 124 merely displays when the shoe 100 should be replaced, it is anticipated that consumers would prefer to have some warning of the expiration of the shoe 100. Accordingly, it is preferable that the display 124 shows the estimated remaining life of the shoe 100 on a relative scale. For visual displays 124, it is preferable that the display 124 is visible in lighting conditions including low light, ambient indoor lighting, and direct sunlight. Audible displays should be readily audible in various environments, yet not so loud as to embarrass or irritate the user.

Prototypes have been constructed using five LEDs 152 embedded in resin, and given a matte finish to increase the effective viewing angle of the LEDs 152, as seen in FIG. 5. The LEDs 152 may be mounted directly on the shoe 100, or may be mounted under a translucent diffusion panel or cover, such as a molded clear plastic to which a frosted surface has been applied. Such diffusion panels or other suitable apparatus may be used to increase the angles from which the LED 152 light is visible.

Many other modifications of the display 124 are possible within the scope of the invention. For example, the number and colors of the LED's may be varied, or, with appropriate substitution of circuitry, other displays 124 may be used, including but not limited to, as electroluminescent displays, liquid crystal displays, flexible liquid crystal displays, or heat activated displays, may be used for display 124. If such panels are used for display 124, the display 124 may provide alpha numeric

information as seen in FIG 6. The use of panels also allows the use of graphics, images, or pictograms rather than alpha numeric symbols on the display 124. If an audible display 124 is desired, a piezo ceramic element may be used to generate the audible signal.

5

In order to reduce power consumption, it is preferable that the status of the shoe 100 be displayed only upon user request. Thus, it is preferable that a switch or button 128 be incorporated in the shoe 100 for activating the display 124. A large number of such buttons or switches are known. The preferred button 128 will be
10 small, inexpensive, easily customizable for different shoe designs, waterproof, dust proof, impact resistant, and will provide tactile feedback when activated. In prototypes, a snap dome switch mounted to a flex circuit has been found acceptable for use.

15

In use, the user wears the shoe 100 like any other shoe 100. No on/off switch is necessary, as the electronics are preferably activated by the receipt of signals from the impact sensors 120. The impact sensors 120 respond to the various impacts experienced by the shoe 100 and send an electrical signal with a signal magnitude that varies depending on the force of the impact strength to the resistor network 142. The
20 resistor network 142 allows the differentiation of the signal by signal strength and converts the analog signal received from the sensors 120 to a signal intended to be detected by digital circuitry, as previously described, and sends the signal to the microprocessor 140. The microprocessor 140 applies pre-programmed algorithms to generate a numerical value. The algorithms applied are preferably based on data

derived from tests on shoes similar to the shoe 100, or on tests on the materials used in the sole 110 of the shoe 100. This value is added to a sum of such values. The accumulated sum of values represents an estimate of the amount of, or accumulation of, wear on the shoe 100. When the display 124 button is depressed, the current sum
5 of values is compared against a pre-determined threshold value. If the threshold has been exceeded, the display 124 will indicate visually or audibly that the shoe 100 must be replaced. In preferred embodiments if the sum is less than the threshold value, the display 124 will indicate an approximate percentage of the life of the shoe 100 remaining.

10

In alternate embodiments the microprocessor 140 may separately sum the wear in different parts of the sole 110 of the shoe 100. For example, it may be desirable to separately track the accumulation of wear on the heel portion of the sole 110 of the shoe 100 and on the portion of the sole 110 of the shoe 100 under the ball of the foot,
15 so that if the shock absorbing ability of one portion of the sole 110 expires before the other, the user may be informed that the shoe should be replaced.

(a) providing a pre-determined numerical value; (b) receiving a signal from an impact sensor; (c) applying an algorithm to derive a value; (d) adding the numerical
20 value of step (c) to a sum of such values to create a new value; (e) comparing the new value of step (d) to the pre-determined value of step (a); (f) estimating the remaining life of the shock absorbing ability of the shoe based on the results of the comparison in step (e).

The method of the invention may also comprise the step of (g) displaying the remaining life of the shock absorbing capability of the shoe based on the results of the comparison in step (f). In another embodiment, the signal from the sensor may be conditioned before step (b), preferably by using a resistor divider network. Also, the method of the invention may be performed separately for separate sensors.

To those skilled in the art, many changes and modifications will be readily apparent from consideration of the foregoing description of a preferred embodiment without departure from the spirit of the present invention; the scope thereof being more particularly pointed out by the following claims. The description herein and the disclosures hereof are by way of illustration only and should not be construed as limiting the scope of the present invention which is more particularly pointed out by the following claims. For example, the invention has been disclosed in the context of an athletic shoe, however, the invention may be incorporated in to many other kinds of shoes or other footwear.

CLAIMS

What is claimed is:

- 1 1. A shoe including a sole having a shock absorbing capability, and a life span of
 2 the shock absorbing capability, comprising:
 3
 4 at least one sensor responsive to impacts experienced by the shoe, and capable of
 5 producing an electric current,
 6
 7 operational circuitry in communication with the sensor, the operational circuitry
 8 capable of manipulating data received from the sensor to estimate a remaining life of
 9 the shock absorbing capabilities of the shoe, and
 10
 11 a display apparatus in communication with the operational circuitry.
- 1 2. The shoe of claim 1 wherein the sensor is also used as a power source.
- 1 3. The shoe of claim 1 further comprising a power source.
- 1 4. A shoe including a sole having a shock absorbing capability, and a life span of
 2 the shock absorbing capability, comprising:
 3
 4 at least one sensor responsive to impacts experienced by the shoe,

5
6 a resistor network in communication with the sensor,
7
8 a microprocessor in communication with the resistor network, the microprocessor
9 capable of manipulating the signal received from the sensor through the resistor
10 network to estimate a remaining life of the shock absorbing capabilities of the shoe,
11
12 a power source, and
13
14 a display apparatus in communication with the microprocessor.

1 5. The shoe of claim 4 wherein the sensor sends a signal through the resistor
2 network to the operational circuitry, and a strength of the signal varies depending on
3 the force of an impact experienced by the sensor.

1 6. The shoe of claim 4 wherein the sensor comprises a piezoelectric element.

1 7. The shoe of claim 4 wherein shoe comprises at least two sensors.

1 8. The shoe of claim 7 wherein at least one sensor is located proximate a heel
2 portion of the sole of the shoe, and at least one sensor is located proximate a toe
3 portion of sole of the shoe.

1 9. The shoe of claim 6 wherein the sensor further comprises a rigid body
2 positioned proximate the piezoelectric element to enhance the deformation of the
3 piezo element.

1 10. The shoe of claim 4 wherein the resistor network converts the signal to a
2 useable voltage and converts the signal to a form sensed by digital circuitry.

1 11. The shoe of claim 10. wherein the resistor network sends signals to the
2 operational circuitry that vary depending on the strength of the signal received from
3 the sensor.

1 12. The shoe of claim 4 wherein the display is a visual display.

1 13. The shoe of claim 4 wherein the display is an audible display.

1 14. The shoe of claim 4 wherein the display is a tactile display.

1 15. The shoe of claim 4, wherein the display is selected for the group consisting
2 of: light emitting diodes, electroluminescent displays, liquid crystal displays, flexible
3 liquid crystal displays, or heat activated displays.

1 16. The shoe of claim 4 wherein the display is in alphanumeric form.

1 17. The shoe of claim 4 wherein the display comprises one or more graphics.

1 18. The shoe of claim 4 further comprising a button to activate the display.

1 19. The shoe of claim 4 wherein the power source is a piezoelectric element.

1 20. The shoe of claim 4 wherein the power source is the sensor.

1 21. The shoe of claim 14 wherein the audible display comprises a piezoelectric
2 speaker element.

1 22. A method for estimating the approximate useful remaining life of the shock
2 absorbing capability of the shoe, wherein the shoe comprises at least one sensor,
3 operational circuitry in communication with the sensor, wherein the operational
4 circuitry is capable of manipulating data received from the sensor to estimate the
5 remaining life of the shock absorbing capabilities of the shoe, a power source
6 electrically coupled to the operational circuitry, and a display in communication with
7 the operational circuitry capable of displaying information related to the remaining
8 useful life of the shock absorbing capabilities of the shoe; the method comprising the
9 following steps:

10

11 (a) Providing a pre-determined numerical value

12

13 (b) Receiving a signal from a force sensor

14

15 (c) Applying an algorithm to the force signal to derive a value

16

17 (d) Adding the numerical value of step (c) to a sum of such values to create a new
18 value.

19

20 (e) Comparing the new value of step (d) to the pre-determined value of step (b).

21

22 (f) estimating the remaining life of the shock absorbing ability of the shoe based
23 on the results of the comparison in step (e).

1 23. The method of claim 22 further comprising the step of (g) displaying the
2 remaining life of the shock absorbing ability of the shoe based on the results of the
3 comparison in step (f).

1 24. The method of claim 22 wherein steps (a) through (f) are performed separately
2 for separate sensors.




Fig. 1

2 / 5




FIG. 2

3 / 5




FIG. 3a




FIG. 3b




FIG. 4

5/5




FIG. 5




FIG. 6

10/018897

531 Rec'd PCT/PTC 15 DEC 2001

CERTIFICATION UNDER 37 CFR 1.10

EG605895497US

December 15, 2001

"Express Mail" mailing number

Date of Deposit

United States

I hereby certify that this Patent Application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

[Signature]
(Signature of person mailing)

DOCKET NO. PLI-1052

SERIAL NO.

FILING DATE:

FOR : SHOE WEAR INDICATOR

U.S. Patent Application including Declaration
\$406.00 check enclosed plus 5 sheets
drawings in duplicate

POSTAGE = 2.00




FIG. 1

2 / 5




FIG. 2

3 / 5




FIG. 3a




FIG. 3b

4 / 5




FIG. 4

5 / 5




FIG. 5




FIG. 6

Please type a plus sign(+) inside this box



PTO/SB/81 (10-00)

Approved for use through 10/31/2002. OMB 0651-0035

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it display a valid OMB control number.

**POWER OF ATTORNEY OR
AUTHORIZATION OF AGENT**

Application Number

Filing Date

First Named Inventor

MYERS, Steven

Group Art Unit

Examiner Name

Attorney Docket Number

PLI-1052

I hereby appoint:

☒ Practitioners at Customer Number

24984

OR

☐ Practitioner(s) named below:

Name	Registration Number
Albert O. Cota	29,291

as my/our attorney(s) or agent(s) to prosecute the application identified above, and to transact all business in the United States Patent and Trademark Office connected therewith.

Please change the correspondence address for the above-identified application to:

☐ The above-mentioned Customer Number.

OR

☒ Firm or
Individual Name

Steven Myers

Michael Strasser

Address

943 Emerson Street

3312 Los Huertas Road

Address

943 Emerson Street

Lafayette, CA 94549

City

Palo Alto

State California

Zip

94301

Country

United States of America

Telephone

(650) 279-7098

Fax

I am the:

☒ Applicant/Inventor.☐ Assignee of record of the entire interest. See 37-CFR 3.71.

Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96).

SIGNATURE of Applicant or Assignee of Record

Name	Steven Myers	Michael Strasser
Signature		
Date	12/13/01	12/13/01

NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more than one signature is required, see below.

☐ Total of _____ forms are submitted.

Burden Hour Statement: This form is estimated to take 3 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

(1 January 2001)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	PLI-1052
	First Named Inventor	Steven Myers
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	
	Group Art Unit	
	Examiner Name	

As a below named inventor, I hereby declare that:

My residence, mailing address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SHOE WEAR INDICATOR

(Title of the Invention)

the specification of which

☐ Is attached hereto

OR

☒ was filed on (MM/DD/YYYY)

as United States Application Number or PCT International

Application Number PCT/US00/4024⁴ and was amended on (MM/DD/YYYY) 8 September 2000 (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT International filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or any PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 21 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

(1 January 2001)

DECLARATION — Utility or Design Patent Application

Direct all correspondence to: ☐ Customer Number or Bar Code Label 24984 OR ☐ Correspondence address below

Name Albert O. Cota

Address 5460 White Oak Avenue, Suite A-331

Address 5460 White Oak Avenue, Suite A-331

City Encino State California ZIP 91316

United States of America Country Telephone (818) 368-4332 Fax (818) 368-4332

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF SOLE OR FIRST INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any]) Steven Family Name or Surname Myers

Inventor's Signature [Signature] Date 12/13/01

Residence: City Palo Alto State CA U.S.A. Country US Citizenship US

Mailing Address 943 Emerson Street

Mailing Address 943 Emerson Street

City Palo Alto State CA ZIP 94301 Country U.S.A.

NAME OF SECOND INVENTOR: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any]) Michael Family Name or Surname Strasser

Inventor's Signature [Signature] Date 12/13/01

Residence: City Lafayette State CA U.S.A. Country US Citizenship US

Mailing Address 3312 Los Huertas Road

Mailing Address 3312 Los Huertas Road

City Lafayette State CA ZIP 94549 Country U.S.A.

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.